

**2200LKY****ALÇAK AKIŞ****ÜRÜN AÇIKLAMASI / DESCRIPTION :**

Laboratuvar regülatörü hassas cihazlarda kullanılan posta regülatörü

ÜRÜN AÇIKLAMASI / DESCRIPTION :

Postal regulator used in laboratory regulator precision devices

**TEKNİK DETAY
TECHICAL DETAIL**

TÜR KIND	GAZ GAS
GÖVDE MALZEME MATERIAL	Bakır Çinko karışım
GİRİŞ / ÇIKIŞ AĞIZLARI INLET AND OUTLET THREAD	G 1/4"
GİRİŞ BASINCI (BAR) INLET PRESSURE (BAR)	(0-40 bar)
ÇALIŞMA BAR ARALIĞI BAR RANGE	(0-10 bar)
TASARIM BASINCI DESIGN PRESSURE	DEĞİŞKEN VARIABLE
DİYAFRAM VE CONTALARI DIAPHRAGM AND SEALS	NPR
ÇALIŞMA ISI ARALIĞI TEMPERATURE RANGE	(-20 C') - (+70 C')
KUBBE YÜKLEME AĞZI DOME LOADING SIDE	Kurma
KATMANLARI LAYERS	1
İÇ ÇAP INNER DIAMETER	5 mm
MUKAVEMET TESTİ STRENGTH TEST	%100
TEMİZLEME CLEANING	KİMYASAL MALZEME CHEMICAL MATERIAL
MUAYENE GEREKSİNİMİ TESTING REQUIREMENTS	STANDART GAZ STANDART GAS
KİMLİK VE İŞARETLEME IDENTITY AND MARKING	DARBELİ BASKI IMPACT PRINTING

**GAZ TÜRÜ
TYPE OF GAS****Giriş / Çıkış
In / Out****Çıkış Barı
Out Pressure****P1=10 Bar
P2=10 Bar****OKSİJEN**
OXYGEN**G Fittings**
female

0-10 bar

29 nm3/h

AZOT
NITROGEN**G Fittings**
female

0-10 bar

32 nm3/h

DOĞALGAZ
NATURAL GAS**G Fittings**
female

0-10 bar

51,5 nm3/h

KURUHAVA
AIR**G Fittings**
female

0-10 bar

31 nm3/h

**UYUMLU GAZLAR
TYPE OF GAS****EBATLAR
SIZES**

OKSİJEN / OXYGEN

E 121x B 170 x D 142

SOY GAZ / INERT GAS

YANICI GAZ / FUEL GAS

SİKİŞTİRİLMİŞ GAZ / COMPRESSED GAS

